

# Ups Cyberpower 3000Va/2700W Online



Preço do produto:

**677,48 € imposto  
incluído**

## Breve descrição do produto:

Ups Cyberpower 3000Va/2700W Online

## Descrição do produto:

Model  
OLS3000E

Capacity(VA/W)  
3000VA / 2700W

Typology  
Online (Double Conversion)

Energy-Saving Technology  
Yes, ECO Mode Efficiency > 95%

Input

### Voltage Range

120~139Vac for 0~25% Load

140~159Vac for 0~50% Load

160~179Vac for 0~75% Load

180~280Vac for 0~100% Load

### Input Type

IEC C20

### Frequency Range

40~70Hz

### Output

#### UPS Outlets (Numbers)

(2+2) IEC C13, (1) IEC C19, Terminal Block

#### On Battery Output Voltage

Pure Sine Wave at 208, 220, 230, 240 Vac  
(Configurable)

#### On Battery Output Voltage Distortion (@Nominal Battery Voltage)

±3%(Linear Load), ±5%(Non-Linear Load)

#### On Battery Output Frequency

50 Hz / 60 Hz (Auto-Sensing or Configurable) ±  
0.5%

#### Transfer Time (Typical)

0ms

#### Overload Protection

AC Mode: Warning only @ 110%>Load>105%,  
Transfer to bypass after 60sec @

---

120%>Load>110%,  
Transfer to bypass immediately @ Load>120%  
Battery Mode: Warning only @  
110%>Load>105%,  
Shutdown after 10sec @ 120%>Load>110%,  
Shutdown immediately @ Load>120%  
Bypass Mode: Warning only @  
130%>Load>105%,  
Shutdown immediately @ Load>130%

## Surge Protection and Filtering

Surge Protection  
Yes

DSL/Phone/Fax/Modem protection  
RJ11/RJ45(One In/One Out)

Short Circuit Protection  
UPS Output Cut off Immediately or Circuit  
Breaker Protection

## Physical

Dimensions(H x W x D)(mm)  
337 x 196 x 416

Weight(kg)  
28.2

## Battery

Sealed Maintenance Free Lead Acid Battery  
(6) 12V / 9AH

Configurable External Battery Pack (Max.)

---

3

Typical Recharge Time  
5

Runtimes

Half load-Full load (mins)  
14/5

Status Indication

Indicators  
Power On, Line Mode, Battery Mode, Bypass Mode, ECO Mode,C/F Mode, Fault, Replace Battery

Audible Alarms  
Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery

Communication

Power Management Software  
PowerPanel® Business Edition

Management

Self-Test  
Yes

Auto-Charge/Auto-Restart  
Yes

---

Auto-Overload Recovery

Yes

Cold Start(DC Start)

Yes

Connectivity Ports

(1) Serial Port (RS232), (1) USB Port, (1)

EPO/ROO

SNMP/HTTP Capable

Optional